

CONNECTED
HEAT PUMP

WLAN ADAPTER
INCLUDED

Daikin Altherma 3 M



The power pact



E(B/D)LA-D series

Daikin Altherma 3 M
Ideal for renovations



Daikin Residential Controller App

NEW

Now available with
voice control



Daikin Altherma 3 M
Suitable for new buildings



Daikin Altherma 3 M

Air-to-water monobloc system that provides **heating only** and is ideal for indoor spaces that have limited room

- › WLAN cartridge connection (optional)
- › Possible to combine with domestic hot water tanks
- › Heating only air-to-water heat pump
- › Monobloc all-in-one concept including all hydraulic parts
- › An optional built-in 3 kW electric back-up heater or a separate back-up heater kit are available for additional heating
- › Available in one phase and three phase



Single Unit					EDLA	09D(3)V3/D(3)W1	11D(3)V3/D(3)W1	14D(3)V3/D(3)W1	16D(3)V3/D(3)W1	
Heating capacity	Nom.				kW	9.37 (1) / 9.00 (2)	10.6 (1) / 9.82 (2)	12.0 (1) / 12.5 (2)	16.0 (1) / 16.0 (2)	
Power input	Heating	Nom.			kW	1.91 (1) / 2.43 (2)	2.18 (1) / 2.68 (2)	2.46 (1) / 3.42 (2)	3.53 (1) / 4.56 (2)	
COP						4.91 (1) / 3.71 (2)	4.83 (1) / 3.66 (2)	4.87 (1) / 3.64 (2)	4.53 (1) / 3.51 (2)	
 Space heating	Average climate water outlet 55 °C	General	ηs (Seasonal space heating efficiency)			133	130	132	130	
			SCOP			3.39	3.32	3.37	3.33	
			Seasonal space heating eff. class			A++				
	Average climate water outlet 35 °C	General	ηs (Seasonal space heating efficiency)			186	182			
			SCOP			4.72	4.64	4.62		
			Seasonal space heating eff. class			A+++				
Casing						Silver				
Material						Polyester painted galvanised steel plate				
Dimensions	Unit	HeightxWidthxDepth			mm	870 x 1,380 x 460				
Weight	Unit				kg	DV3/DW1: 147, D3V3/D3W1: 149				
Compressor						1				
Type						Hermetically sealed swing compressor				
Operation range	Heating	Ambient	Min.~Max.		°CWB	DV3/DW1: -25 ~ 25, D3V3/D3W1: -25 ~ 35				
		Water side	Min.~Max.		°C	DV3/DW1: 9 ~ 60, D3V3/D3W1: 15 ~ 60				
Operation range	Domestic hot water	Ambient	Min.~Max.		°CDB	-25 ~ 35				
		Water side	Min.~Max.		°C	25 ~ 55				
Refrigerant	Type					R-32				
	GWP					675.0				
	Charge				kg	3.80				
	Charge				TCO2Eq	2.57				
	Control					Expansion valve				
Sound power level (3)	Heating	Nom.			dBA	62				
Power supply	Name/Phase/Frequency/Voltage				Hz/V	V3/1~/50/230 - W1/3~/50/400				
Current	Recommended fuses				A	32/16				

(1) Ta DB/WB 7 °C/6 °C - LWC 35 °C (DT = 5 °C) | (2) Ta DB/WB 7 °C/6 °C - LWC 45 °C (DT = 5 °C) | (3) According to EN14825 This product contains fluorinated greenhouse gases.

Daikin Altherma 3 M

Reversible air-to-water monobloc system that provides **heating and cooling**, and is ideal for indoor spaces that have limited room

- › WLAN cartridge connection (optional)
- › Possible to combine with domestic hot water tanks
- › Heating and cooling air-to-water heat pump
- › Monobloc all-in-one concept including all hydraulic parts
- › An optional built-in 3 kW electric back-up heater or a separate back-up heater kit are available for additional heating
- › Available in one phase and three phase



Single Unit				EBLA	09D(3)V3/D(3)W1	11D(3)V3/D(3)W1	14D(3)V3/D(3)W1	16D(3)V3/D(3)W1
Heating capacity	Nom.			kW	9.37 (1) / 9.00 (2)	10.6 (1) / 9.82 (2)	12.0 (1) / 12.5 (2)	16.0 (1) / 16.0 (2)
Power input	Heating	Nom.		kW	1.91 (1) / 2.43 (2)	2.18 (1) / 2.68 (2)	2.46 (1) / 3.42 (2)	3.53 (1) / 4.56 (2)
COP					4.91 (1) / 3.71 (2)	4.83 (1) / 3.66 (2)	4.87 (1) / 3.64 (2)	4.53 (1) / 3.51 (2)
Cooling capacity	Nom.			kW	9.35 (3) / 9.10 (4)	11.6 (3) / 11.5 (4)	12.8 (3) / 12.7 (4)	14.0 (3) / 15.3 (4)
Power input	Cooling	Nom.		kW	2.79 (3) / 1.71 (4)	3.56 (3) / 2.17 (4)	4.06 (3) / 2.51 (4)	4.58 (3) / 3.24 (4)
EER					3.35 (3) / 5.34 (4)	3.26 (3) / 5.31 (4)	3.16 (3) / 5.04 (4)	3.06 (3) / 4.74 (4)
SEER					5.62 (5)	5.79 (5)	5.71 (5)	5.59 (5)
 Space heating	Average climate water outlet 55 °C	General	ηs (Seasonal space heating efficiency)		135	132	134	132
			SCOP		3.44	3.37	3.42	3.37
			Seasonal space heating eff. class	A++				
	Average climate water outlet 35 °C	General	ηs (Seasonal space heating efficiency)		190	186	185	
			SCOP		4.82	4.73	4.70	4.69
			Seasonal space heating eff. class	A+++				
Casing	Colour				Silver			
	Material				Polyester painted galvanised steel plate			
Dimensions	Unit	HeightxWidthxDepth		mm	870 x 1,380 x 460			
Weight	Unit			kg	DV3/DW1: 147, D3V3/D3W1: 149			
Compressor	Quantity				1			
	Type				Hermetically sealed swing compressor			
Operation range	Heating	Ambient	Min.~Max.	°CWB	DV3/DW1: -25 ~ 25, D3V3/D3W1: -25 ~ 35			
		Water side	Min.~Max.	°C	DV3/DW1: 9 ~ 60, D3V3/D3W1: 15 ~ 60			
Operation range	Cooling	Ambient	Min.~Max.	°CDB	10 ~ 43			
		Water side	Min.~Max.	°C	5 ~ 22			
Operation range	Domestic hot water	Ambient	Min.~Max.	°CDB	-25 ~ 35			
		Water side	Min.~Max.	°C	25 ~ 55			
Refrigerant	Type				R-32			
	GWP				675.0			
	Charge			kg	3.80			
	Charge			TCO2Eq	2.57			
	Control				Expansion valve			
Sound power level (5)	Heating	Nom.		dBA	62			
Power supply	Name/Phase/Frequency/Voltage			Hz/V	V3/1~/50/230 - W1/3~/50/400			
Current	Recommended fuses			A	32/16			

(1) Ta DB/WB 7 °C/6 °C - LWC 35 °C (DT = 5 °C) | (2) Ta DB/WB 7 °C/6 °C - LWC 45 °C (DT = 5 °C) | (3) Cooling: EW 12 °C; LW 7 °C; ambient conditions: 35 °CDB | (4) Cooling: EW 23 °C; LW 18 °C; ambient conditions: 35 °CDB | (5) According to EN14825. This product contains fluorinated greenhouse gases.



CLIMATE DESIGN D.O.O. Javorska 6, 11226 Beograd, Tel:
+38162290789, +38162290599

E-mail: veleprodaja@climatedesign.rs, www.climatedesign.rs

