



LEO HD

Air heating and ventilation
in special purpose buildings



Water fan heaters



Air flow

up to 3800 m³/h



Heating capacity

up to 38,4 kW



Weight

11,3 – 25,3 kg



Corrosion class

C5-h according to
12944-6:2018

What is LEO HD?

The LEO HD fan heater is designed for building structures that require equipment with increased resistance to environmental conditions. The water heat exchanger installed in the heater is covered with special pigmented polyurethane coating PoluAl XT Blygold, which is characterised by very high resistance to corrosion and chemical compounds.

Types of units

- LEO HD AC IP54 – fan heater with AC fan
- LEO HD EC IP54 – fan heater with EC fan
- LEO HD AC IP66 – fan heater with AC fan with higher protection level IP66

All available models can be manufactured in one of two types of casings: expanded polypropylene (EPP) or stainless steel INOX AISI316L.




Application

- washing facilities
- wastewater treatment plants
- galvanizing plants
- food industry buildings
- greenhouses
- chemical industry
- maritime industry

Types of unit

A full series of LEO HD fan heaters means that you can choose the ideal solution for the needs of your building. FLOWAIR offers fan heater models with a wide range of heating capacity, whose parameters have been confirmed by an independent testing laboratory.



Heating power range specified at the following parameters:

min. – 1st fan speed, heating medium temperature 40/30°C, air temperature at unit inlet 20°C;

max. – 3rd fan speed, heating medium temperature 90/70°C, air temperature at device inlet 0°C.

As many as 10 fan heater models, in 2 casing versions! INOX console included! Match the device to the building's requirements even better

INOX — casing made of acid-resistant steel AISI316L. Standard design.

EPP — expanded polypropylene casing. Standard design.



BLYGOLD heat exchanger


Standard heat exchangers are vulnerable to intense corrosion due to the nature of their design, which often involves different metals with incompatible chemical properties. The combination of these metals can cause galvanic corrosion, especially when they are exposed to moisture and other substances. In addition, heat exchangers are often placed in environments featuring contaminated air, which can accelerate the corrosion process through chemical reactions.

The **Blygold coating**, as used in LEO HD, is an effective solution that provides lasting corrosion protection for heat exchangers, while maintaining heat transfer efficiency and minimal impact on pressure drop.



Design of LEO HD

Thanks to its clever design and the Blygold coating used on the exchangers, the LEO HD device is ideal for special purpose buildings.



Dimensions





Table of PoluAl XT coating resistance


Name	Max. concentration [ppm]	Other	
Inorganic acids			
Arsenic acid	641	Carbon disulphide160	
Boric acid		Hydrogen peroxide320	
Hydrogen carbonate		Hydrogen sulphide20	
Chromic acid		Chlorine64	
Sulphonic acid			
Bromic acid	320	Organic acids	
Hydrochloric acid		Acetic acid	
Hydrogen fluoride		Benzoic acid	
Hydrogen sulphide		Lactic acid	
Nitric acid		Phenols	
Sulphuric acid		Citric acid	
Phosphoric acid		Fatty acids	
Perchloric acid		Stearic acid	
Selenic acid		Hydrocyanic acid	
		Malic acid	
Bases		Margaric acid320	
Ammonia	160	Picric acid	
Sodium hydroxyde	20	Oleic acid	
Potassium hydroxide solution		Oxalic acid	
Lithium hydroxide		Sulphamic acid	
Calcium hydroxide		Palmitic acid	
Magnesium hydroxide		Tannin	
		Phthalic acid	
		Valerian acid	
		Salicylic acid	
Alts and aqueous solutions		Formic acid80	
Sodium salt	640	Propionic acid	
Potassium salts			
Calcium salt		Ketones and aldehydes	
Aluminium salts		Acetone	
Ammonium salts		Acetaldehyde	
Barium salts		Benzaldehyde	
Copper salts		Formaldehyde	
Lead salts		Salicylaldehyde320	
Lithium salts		Diisobutyl ketone	
Magnesium salts		Methylethylketone	
Mercury salts		Butanal	
Lithopone		Crotonaldehyde	
Hydroquinone			
Iron salts			
			Alcohols
Aromatic hydrocarbons			Methanol
Xylene	640	Ethanol	
Toluene		Isopropanol	
Bitumen		n-Butanol	
Anthracene		Amyl alcohol320	
Benzaferen		Benzyl alcohol	
Benzene		Diacetone alcohol DAA	
Solvent naphtha		Glycerol	
Naphthalene		n- Propanol	
Terpenes		Pentanol	



Technical data, accessories and installation of units

	LEO HD S AC	LEO HD S EC	LEO HD L AC	LEO HD L AC IP66	LEO HD L EC
Step (AC) / Voltage setting [V] (EC)	3 2 1	10 8 6 4	3 2 1	5 4 3 2 1	10 8 6 4
Air flow [m³/h]*	2000 1600 1250	1650 1300 950 600	3800 2400 1400	3800 3500 2930 2300 1400	3000 2750 2850 950
Current consumption [A]	0,6 0,4 0,3	0,55 0,31 0,15 0,1	1,5 1,2 0,6	1,7 1,4 1,2 1,1 0,8	1,3 0,8 0,4 0,2
Power consumption [W]	130 90 70	60 41 22 10	340 240 120	355 293 259 214 158	170 113 56 21
Heating capacity (70 / 50 / 15°C) [kW]	11,8 104 9	10,4 9,2 7,6 5,6	20,8 15,8 11,1	20,8 19,8 17,9 15,4 11,1	1,3 0,8 0,38 0,14
Acoustic pressure level ⁽²⁾ [dB(A)]	54,4 48,8 42	54 46,8 40,7 32,1	62,3 52,6 40,2	62,3 61,3 57,5 52,3 40,2	56 53,1 45,7 36,2
Acoustic power level ⁽³⁾ [dB(A)]	71,4 65,8 59	71 63,8 57,7 49,1	79,2 69,6 57,2	79,2 78,3 74,5 69,3 57,2	73 70,1 62,7 53,2
Max. outlet temperature [°C]	31	37,5	38,5	38,5	41
Max. horizontal isothermal range ⁽⁴⁾ [m]	27	22,5	41	41	33
Max. operating pressure [MPa]	1,6	1,6	1,6	1,6	1,6
Max. heating medium temperature [°C]	120	120	120	120	120
Operating temperature range [°C]	-30 do 60	-30 do 60	-30 do 60	-30 do 60	-30 do 60
Fan type / protection level	AC / IP54	EC / IP54	AC / IP54	AC / IP66	EC / IP54
Rated voltage [V / Hz]	230 / 50	230 / 50	230 / 50	230 / 50	230 / 50
Water connection ["]	½	½	¾	¾	¾
Maximum capacity ⁽¹⁾ [m³ / h]	2000	1650	3800	3800	3000
Casing type	EPP / INOX	EPP / INOX	EPP / INOX	EPP / INOX	EPP / INOX
Weight [kg]	12,4 / 17,2	11,3 / 16,1	18,5 / 24,2	19,4 / 25,3	16,6 / 22,5
Unit weight filled with water [kg]	13,6 / 18,4	12,5 - 17,3	20,5 / 26,4	21,4 / 27,3	18,6 / 24,5
Compatible with heat pump	 HP ready	 HP ready	 HP ready	 HP ready	 HP ready

Installation of the LEO HD fan water heater



Installation accessories

Rotary console (AISI316L)

Allows easy installation at different angles to vertical and horizontal positions.



Ceiling brackets (AISI316L)

Designed for ceiling installation (optional equipment). Easy ceiling installation on pins.



⁽¹⁾ With vertical arrangement of the air blades. For ceiling installation, the installation height should be selected according to the non-isothermal vertical range.

Control and control elements

TS controller – basic version

This is the simplest 3-speed fan control system. The operation of the fan heater is regulated by a 3-speed controller with thermostat.



HMI controller – basic version

This is an advanced 3-speed fan control system with an HMI programmable controller.



T-box controller – BMS version

This is intelligent control tailored to individual needs thanks to the T-box controller with touchscreen display.



TRA+ R55 for IP 66

It's a simple unit setting. TRA provides 5-speed fan speed control, while R55 is an ON/OFF thermostat adapted to a higher IP protection level.



	R55 + TRA	TS controller	HMI controller	T-box controller
Types of regulation/control:				
Manual 3-step air flow regulation		✓	✓	✓
Automatic 3-step air flow regulation			✓	✓
Manual 5-step air flow regulation	✓			
Modes				
Heating / Cooling / Ventilation	✓	✓	✓	✓
Operation in continuous or thermostatic mode	✓	✓	✓	✓
Weekly programmer			✓	✓
BMS			✓	✓
Antifreeze			✓	✓
Integration with FLOWAIR SYSTEM				✓
Weekly programmer for each zone				✓ ⁽¹⁾
Individual settings for each zone				✓ ⁽¹⁾
Individual description of the controlled zone				✓ ⁽¹⁾
Antifreeze for each zone				✓ ⁽¹⁾
IP / Insulation class	55	20	20	20
Max. number of connected units				
Via controller	1	7	5	31
Via additional splitters	n/a	36	36	n/a



Control elements

Wall-mounted temperature sensor

Wall mounted temperature sensor makes it possible to measure the temperature in a different zone than the controller.



Possibility of temperature measurement

Controller	Temperature sensor	The connection of wall mounted temperature sensor
TS	integrated	n/a
HMI	NTC or integrated	to HMI controller
T-box	PT-1000 or integrated	to DRV control module

RX splitters

Splitter of control signal for connection of several LEO HD units with 3-step fans (AC IP54) to a one controller. It is possible to combine max. 3 splitters RX, so that the single controller can control up to 36 units simultaneously.




Max. number of controlled units via single controller


Splitter	LEO HD S AC IP54	LEO HD L AC IP54
1 pcs. RX	12	6
2 pcs. RX	24	12
3 pcs. RX	36	18

Connection diagrams


TS / HMI controller



T-box controller



TRA R55 controller



Accessories


LEO HD

Mixing chamber

Mixing chambers (KM) allow fresh air to be supplied to the room. LEO HD + KM + UVO is the easiest way to create the efficient ventilation in a objects, at the lowest possible energy consumption, without additional systems. The mixing chamber/heater combo is easy to assemble thanks to the matching brackets.




Dimensions



LEO HD S AC IP54 + KM S

LEO HD L AC IP54 + KM L
LEO HD L AC IP66 + KM L

Mixing chamber installation



LEO HD + KM + UVO is the easiest way to the efficient ventilation in a room without the need for additional systems.



The mounting bracket allows the unit to be easily and aesthetically mounted to vertical partitions.

(1) With vertical arrangement of the air blades. For ceiling installation, the installation height should be selected according to the non-isothermal vertical range.

Installation distances

	LEO HD S AC IP54 + KM S	LEO HD L AC IP54 + KM L LEO HD L AC IP66 + KM L
A	max. 3,0	2,5 – 5,0
B	2,5 – 4,0	2,5 – 6,0

Technical data

	LEO HD S AC IP54 + KM S	LEO HD L AC IP54 + KM L LEO HD L AC IP66 + KM L
Max. air flow stream ⁽¹⁾ [m³/h]	1100	2400
Nominal heating power (70/50/16°C, III bieg) [kW]	7,2	14,4
Power supply [V/Hz]	230/50	230/50
Max. Current consumption [A]	0,6	1,5
Max. Power consumption [W]	130	340
IP / Insulation class	54/F	54/F
Max. Acoustic pressure level ⁽²⁾ [dB(A)]	56,3	64,1
Max. Acoustic power level ⁽³⁾ [dB(A)]	71,4	79,2
Horizontal range ⁽⁴⁾ [m]	7,5	13,5
Vertical range ⁽⁵⁾ [m]	3,2	5,0
Max. heating water temperature [°C]	120	120
Max. operating pressure [MPa]	1,6	1,6
Connection	1/2"	3/4"
Weight of unit [kg]	26,8	35,5
Weight of unit filled with water [kg]	28,0	37,5

⁽¹⁾ Capacity with air intake and 100% fresh air – air flow measured in accordance with ISO 5801

⁽²⁾ Acoustic pressure level for a room with average sound absorption, volume 1500 m³, at a distance of 5m from the unit

⁽³⁾ In accordance with EN ISO3744

⁽⁴⁾ Horizontal range of the isothermal air stream, at a speed limit of 0.5 m/s

⁽⁵⁾ Vertical range of non-isothermal air stream at T = 5°C, at a speed limit of 0.5 m/s

Heating capacities

LEO HD

Tw1/Tw2 = 45/35°C					Tw1/Tw2 = 70/50°C					Tw1/Tw2 = 55/45°C				
Tp1	PT	Qw	Δpw	Tp2	Tp1	PT	Qw	Δpw	Tp2	Tp1	PT	Qw	Δpw	Tp2
[°C]	[kW]	[l/h]	[kPa]	[°C]	[°C]	[kW]	[l/h]	[kPa]	[°C]	[°C]	[kW]	[l/h]	[kPa]	[°C]
LEO HD S EC														
V = 1650 m³/h 54,0 db(A) ⁽⁰⁾														
10,0	6,3	550	6,9	21,5	10,0	10,4	454	4,5	29	10,0	8,7	760	11,9	26
15,0	5,1	446	4,8	24	15,0	9,2	403	3,7	32	15,0	7,6	660	9,2	29
20,0	3,9	339	3	27	20,0	8,1	352	2,9	35	20,0	6,4	558	6,8	32
V = 1300 m³/h 46,8 db(A) ⁽⁰⁾														
10,0	5,5	477	5,4	22,5	10,0	9,2	401	3,6	31	10,0	7,7	671	9,5	27,5
15,0	4,5	386	3,7	25	15,0	8,2	357	3	33,5	15,0	6,7	582	7,4	30
20,0	3,4	294	2,3	27,5	20,0	7,1	311	2,3	36	20,0	5,7	493	5,5	33
V = 950 m³/h 40,7 db(A) ⁽⁰⁾														
10,0	4,5	392	3,8	24	10,0	7,6	330	2,6	33,5	10,0	6,3	552	6,7	29,5
15,0	3,7	317	2,6	26,5	15,0	6,7	293	2,1	36	15,0	5,5	479	5,2	32
20,0	2,8	241	1,6	28,5	20,0	5,9	256	1,7	38	20,0	4,7	405	3,9	34,5
V = 600 m³/h 32,1 db(A) ⁽⁰⁾														
10,0	3,3	289	2,2	26,5	10,0	5,6	244	1,5	37,5	10,0	4,7	407	3,9	33
15,0	2,7	234	1,5	28	15,0	5	217	1,2	39	15,0	4,1	354	3	36,5
20,0	2	176	0,9	30	20,0	4,3	189	1	41	20,0	3,5	299	2,3	36,5
LEO HD S AC														
V = 2000 m³/h 54,4 db(A) ⁽⁰⁾														
10,0	7,1	615	8,5	20,5	10,0	11,8	517	5,7	27,5	10,0	9,9	867	15	24,5
15,0	5,7	499	5,8	23,5	15,0	10,5	459	4,6	30,5	15,0	8,6	752	11,6	27,5
20,0	4,4	380	3,6	26,5	20,0	9,2	401	3,6	33,5	20,0	7,3	636	8,6	30,5
V = 1600 m³/h 48,8 db(A) ⁽⁰⁾														
10,0	6,2	540	6,7	21,5	10,0	10,4	454	4,5	29	10,0	8,7	760	11,9	26
15,0	5	437	4,6	24,5	15,0	9,2	403	3,7	32	15,0	7,6	660	9,2	29
20,0	3,8	333	2,9	27	20,0	8,1	352	2,9	35	20,0	6,4	558	6,8	32
V = 1250 m³/h 42,0 db(A) ⁽⁰⁾														
10,0	5,4	465	5,2	22,5	10,0	9	392	3,5	31	10,0	7,5	655	9,1	28
15,0	4,3	377	3,6	25,5	15,0	8	348	2,8	34	15,0	6,5	569	7	30,5
20,0	3,3	287	2,2	28	20,0	7	304	2,2	36,5	20,0	5,5	481	5,2	33
LEO HD L EC														
V = 3000 m³/h 56,0 db(A) ⁽⁰⁾														
10,0	12,2	1063	5,2	22	10,0	20,5	895	3,5	30	10,0	17,4	1517	9,5	27
15,0	9,8	854	3,5	24,5	15,0	18,1	792	2,8	33	15,0	15	1311	7,3	30
20,0	7,4	641	2,1	27,5	20,0	15,7	688	2,2	35,5	20,0	12,7	1103	5,3	32,5
V = 2750 m³/h 53,1 db(A) ⁽⁰⁾														
10,0	11,6	1009	4,7	22,5	10,0	19,4	849	3,2	31	10,0	16,5	1439	8,6	28
15,0	9,3	810	3,2	25	15,0	17,2	752	2,6	33,5	15,0	14,3	1244	6,6	30,5
20,0	7	608	1,9	27,5	20,0	14,9	653	2	36	20,0	12	1047	4,9	33

Tw1/Tw2 = 45/35°C					Tw1/Tw2 = 70/50°C					Tw1/Tw2 = 55/45°C				
Tp1	PT	Qw	Δpw	Tp2	Tp1	PT	Qw	Δpw	Tp2	Tp1	PT	Qw	Δpw	Tp2
[°C]	[kW]	[l/h]	[kPa]	[°C]	[°C]	[kW]	[l/h]	[kPa]	[°C]	[°C]	[kW]	[l/h]	[kPa]	[°C]
V = 1850 m³/h 45,7 db(A)⁽¹⁾														
10,0	9	785	3	24,5	10,0	15,1	662	2,1	34	10,0	12,8	1119	5,5	30,5
15,0	7,3	630	2,1	26,5	15,0	13,4	586	1,7	36,5	15,0	11,1	968	4,2	32,5
20,0	5,4	470	1,2	28,5	20,0	11,6	509	1,3	38,5	20,0	9,4	815	3,1	35
V = 950 m³/h 36,2 db(A)⁽¹⁾														
10,0	5,7	495	1,3	28	10,0	9,6	419	0,9	40	10,0	8,1	708	2,4	35,5
15,0	4,6	395	0,9	29	15,0	8,5	371	0,7	41	15,0	7	612	1,9	36,5
20,0	3,3	289	0,5	30,5	20,0	7,3	321	0,6	42,5	20,0	5,9	516	1,4	38
LEO HD L AC														
V = 3800 m³/h 40,2 db(A)⁽¹⁾														
10,0	14,1	1224	6,7	21	10,0	23,5	1030	4,5	28,5	10,0	20	1747	12,2	25,5
15,0	11,3	983	4,5	24	15,0	20,8	911	3,6	31	15,0	17,3	1509	9,4	28,5
20,0	8,5	738	2,7	26,5	20,0	18,1	791	2,8	34	20,0	14,6	1270	6,9	31,5
V = 2400 m³/h 52,6 db(A)⁽¹⁾														
10,0	10,7	927	4,1	23	10,0	17,9	781	2,8	32	10,0	15,2	1322	7,4	28,5
15,0	8,6	745	2,8	25,5	15,0	15,8	691	2,2	34,5	15,0	13,1	1143	5,7	31
20,0	6,4	558	1,7	28	20,0	13,7	600	1,7	36,5	20,0	11	963	4,2	33,5
V = 1400 m³/h 40,2 db(A)⁽¹⁾														
10,0	7,5	651	2,2	26	10,0	12,6	550	1,5	36,5	10,0	10,7	929	3,9	32,5
15,0	6	522	1,5	27,5	15,0	11,1	487	1,2	38,5	15,0	9,2	804	3	34,5
20,0	4,5	388	0,9	29,5	20,0	9,7	422	0,9	40	20,0	7,8	677	2,2	36
LEO HD L AC IP66														
V = 3800 m³/h 62,3 db(A)⁽¹⁾														
10,0	14,1	1224	6,7	21	10,0	23,5	1030	4,5	28,5	10,0	20	1747	12,2	25,5
15,0	11,3	983	4,5	24	15,0	20,8	911	3,6	31	15,0	17,3	1509	9,4	28,5
20,0	8,5	738	2,7	26,5	20,0	18,1	791	2,8	34	20,0	14,6	1270	6,9	31,5
V = 3500 m³/h 61,3 db(A)⁽¹⁾														
10,0	13,4	1166	6,1	21,5	10,0	22,4	981	4,2	29	10,0	19,1	1664	11,2	26
15,0	10,8	937	4,2	24	15,0	19,8	868	3,3	31,5	15,0	16,5	1438	8,6	29
20,0	8,1	703	2,5	27	20,0	17,2	753	2,6	34,5	20,0	13,9	1210	6,3	31,5
V = 2930 m³/h 57,5 db(A)⁽¹⁾														
10,0	12,1	1049	5,1	22	10,0	20,2	883	3,5	30,5	10,0	17,2	1496	9,2	27,5
15,0	9,7	842	3,4	25	15,0	17,9	781	2,8	33	15,0	14,8	1293	7,1	30
20,0	7,3	632	2,1	27,5	20,0	15,5	678	2,2	35,5	20,0	12,5	1088	5,2	32,5
V = 2300 m³/h 52,3 db(A)⁽¹⁾														
10,0	10,4	902	3,9	23,5	10,0	17,4	761	2,6	32,5	10,0	14,8	1287	7	29
15,0	8,4	725	2,6	25,5	15,0	15,4	673	2,1	34,5	15,0	12,8	1113	5,4	31,5
20,0	6,3	543	1,6	28	20,0	13,4	84	1,7	37	20,0	10,8	937	4	33,5
V = 1400 m³/h 40,2 db(A)⁽¹⁾														
10,0	7,5	651	2,2	26	10,0	12,6	550	1,5	36,5	10,0	10,7	929	3,9	32,5
15,0	6	522	1,5	27,5	15,0	11,1	487	1,2	38,5	15,0	9,2	804	3	34,5
20,0	4,5	388	0,9	29,5	20,0	9,7	422	0,9	40	20,0	7,8	677	2,2	36

V – air flow

PT – heating capacity

Tp1 – inlet air temperature

Tp2 – outlet air temperature

Tw1 – inlet water temperature

Tw2 – outlet water temperature

Qw – water flow rate in heat exchanger

Δpw – water pressure drop in heat exchanger

(1) – acoustic pressure level for a room with average sound absorption, volume 3000m³, at a distance of 5m from the unit



CLIMATE DESIGN D.O.O. Javorska 6, 11226 Beograd,
Tel:+38162290789, +38162290599
E-mail: veleprodaja@climatedesign.rs, www.climatedesign.rs

