

Chillers heat pump

The ultimate in
reliability and flexibility



Air cooled mini inverter heat pump

- Choosing for an R-32 product, reduces the environmental impact with 68% compared to R-410A and leads directly to lower energy consumption thanks to its high energy efficiency
- Inverter chiller
- Hermetically sealed swing inverter compressor
- New casing for the outdoor units
- Separate MMI-2 controller for indoor installation



Swing compressor

EW(A-Y)A004-008DV3P_R

Heating & Cooling				EWYA-D	004DV3P	006DV3P	008DV3P
Space cooling	A Condition Pdc			kW	-		
	35°C			%	-		
SEER				-			
 Space heating	Average climate water outlet 35°C	General	SCOP	Seasonal space heating eff. class	4.54	4.52	4.61
					A+++		
Cooling capacity	Nom.			kW	4.86(1)/4.52(2)	5.83(1)/5.09(2)	6.18(1)/5.44(2)
Heating capacity	Nom.			kW	4.30(1)/4.60(2)	6.00(1)/5.90(2)	7.50(1)/7.80(2)
Power input	Cooling	Nom.		kW	0.820(1)/1.36(2)	108(1)/155(2)	119(1)/173(2)
	Heating	Nom.		kW	0.840(1)/1.26(2)	124(1)/169(2)	163(1)/2.23(2)
Capacity control	Method			Variable (inverter)			
EER					5.91(1)/3.32(2)	5.40(1)/3.28(2)	5.19(1)/3.14(2)
COP					5.10(1)/3.65(2)	4.85(1)/3.50(2)	4.60(1)/3.50(2)
Dimensions	Unit	Height		mm	770		
		Width		mm	1,250		
		Depth		mm	362		
Weight	Unit			kg	88.0		
Water heat exchanger	Type				Plate heat exchanger		
	Water volume			l	1		
Air heat exchanger	Type				-		
Compressor	Type				Hermetically sealed swing compressor		
	Quantity				1		
Fan	Type				Propeller fan		
	Quantity				1		
	Air flow rate	Cooling	Nom.	m³/min	-		
Heating		Nom.	m³/min	-			
Sound power level	Cooling	Nom.		dBA	61.0(1)	62.0(1)	
	Heating	Nom.		dBA	58.0(1)	60.0(1)	62.0(1)
Sound pressure level	Cooling	Nom.		dBA	48.0(1)	49.0(1)	50.0(1)
	Heating	Nom.		dBA	44.0(1)	47.0(1)	49.0(1)
Operation range	Air side	Cooling	Min.~Max.	°CDB	10(3)~43		
		Heating	Min.~Max.	°CDB	-25~25		
Refrigerant	Type/GWP				R-32/675.0		
	Charge			kg	135		
	Control				-		
	Circuits	Quantity			-		
Refrigerant charge	Per circuit			kg	-		
Unit	Running current	Max		A	-		
Power supply	Phase/Frequency/Voltage			Hz/V	1~/50/230 +/-10%		

(1)Condition 1: cooling Ta 35°C - LWE 18°C (DT = 5°C); heating Ta DB/WB 7°C/6°C - LWC 35°C (DT = 5°C) | (2)Condition 2: cooling Ta 35°C - LWE 7°C (DT = 5°C); heating Ta DB/WB 7°C/6°C - LWC 45°C (DT = 5°C) |

(3)For more details, see operation range drawing | (4)Cooling: EW 12°C; LW 7°C; ambient conditions: 35°CDB | (5)Cooling: EW 23°C; LW 18°C; ambient conditions: 35°CDB |

(6)Condition: Ta DB/WB 7°C/6°C - LWC 35°C (DT = 5°C) | (7)Condition: Ta DB/WB 7°C/6°C - LWC 45°C (DT=5°C) | (8)According to EN14825 | Depends on operation mode, refer to installation manual.

Air cooled mini inverter heat pump

- Choosing for an R-32 product, reduces the environmental impact with 68% compared to R-410A and leads directly to lower energy consumption thanks to its high energy efficiency
- Inverter chiller
- Hermetically sealed swing inverter compressor
- New casing for the outdoor units
- Separate MMI-2 controller for indoor installation



EWAA-EWYA-D_R

Heating & Cooling				EWYA-D	009DV3P	011DV3P	014DV3P	016DV3P	
Space cooling	A Condition Pdc 35°C			kW	9.35	116	128	14.0	
	ηs,c			%	222	229	226	221	
SEER					5.62(8)	5.79(8)	5.71(8)	5.59(8)	
Space heating	 Average climate water outlet 35°C	General	SCOP		4.82	4.73	4.70	4.69	
			Seasonal space heating eff. class	A+++					
Cooling capacity		Nom.			kW	9.35(4)/9.10(5)	116(4)/115(5)	128(4)/127(5)	14.0(4)/15.3(5)
Heating capacity		Nom.			kW	9.37(6)/9.00(7)	10.6(6)/9.82(7)	120(6)/125(7)	16.0(6)/16.0(7)
Power input	Cooling	Nom.		kW	2.79(4)/1.71(5)	3.56(4)/2.17(5)	4.06(4)/2.51(5)	4.58(4)/3.24(5)	
	Heating	Nom.		kW	1.91(6)/2.43(7)	2.18(6)/2.68(7)	2.46(6)/3.42(7)	3.53(6)/4.56(7)	
Capacity control	Method				Variable (inverter)				
EER					3.35(4)/5.34(5)	3.26(4)/5.31(5)	3.16(4)/5.04(5)	3.06(4)/4.74(5)	
COP					4.91(6)/3.71(7)	4.83(6)/3.66(7)	4.87(6)/3.64(7)	4.53(6)/3.51(7)	
Dimensions	Unit	Height		mm	870				
		Width		mm	1,380				
		Depth		mm	460				
Weight	Unit			kg	147				
Water heat exchanger	Type				Plate heat exchanger				
	Water volume			l	2				
Air heat exchanger	Type				High efficiency fin and tube type with integral subcooler				
Compressor	Type				Hermetically sealed swing inverter compressor				
	Quantity				1				
Fan	Type				Propeller fan				
	Quantity				1				
	Air flow rate	Cooling	Nom.	m³/min	63	70	85		
		Heating	Nom.	m³/min	48.0	55.8	70.4	85.0	
Sound power level	Cooling	Nom.		dBA	65.5	67.0	69.0		
	Heating	Nom.		dBA			-		
Sound pressure level	Cooling	Nom.		dBA	44.0	47.7	50.8	51.0	
	Heating	Nom.		dBA			-		
Operation range	Air side	Cooling	Min.~Max.	°CDB	10~43				
		Heating	Min.~Max.	°CDB	-25~25				
Refrigerant	Type/GWP				R-32/675.0				
	Charge			kg	-				
	Control				Electronic expansion valve				
	Circuits	Quantity			1				
Refrigerant charge	Per circuit			kg	3.80				
Unit	Running current	Max		A	30.8				
Power supply	Phase/Frequency/Voltage			Hz/V	1~/50/230				

(1) Condition 1: cooling Ta 35°C - LWE 18°C (DT = 5°C); heating Ta DB/WB 7°C/6°C - LWC 35°C (DT = 5°C) | (2) Condition 2: cooling Ta 35°C - LWE 7°C (DT = 5°C); heating Ta DB/WB 7°C/6°C - LWC 45°C (DT = 5°C) |

(3) For more details, see operation range drawing | (4) Cooling: EW 12°C; LW 7°C; ambient conditions: 35°CDB | (5) Cooling: EW 23°C; LW 18°C; ambient conditions: 35°CDB |

(6) Condition: Ta DB/WB 7°C/6°C - LWC 35°C (DT = 5°C) | (7) Condition: Ta DB/WB 7°C/6°C - LWC 45°C (DT = 5°C) | (8) According to EN14825 | Depends on operation mode, refer to installation manual.

Air cooled mini inverter heat pump

- Choosing for an R-32 product, reduces the environmental impact with 68% compared to R-410A and leads directly to lower energy consumption thanks to its high energy efficiency
- Inverter chiller
- Hermetically sealed swing inverter compressor
- New casing for the outdoor units
- Separate MMI-2 controller for indoor installation



EWAA-EWYA-D_R

Heating & Cooling				EWYA-D	009DW1P	011DW1P	014DW1P	016DW1P
Space cooling	A Condition Pdc 35°C			kW	9.35	11.6	128	14.0
	ηs,c			%	222	229	226	221
SEER					5.62(5)	5.79(5)	5.71(5)	5.59(5)
 Space heating	Average climate water outlet 35°C	General	SCOP	4.82	4.73	4.70	4.69	
			Seasonal space heating eff. class	A+++				
Cooling capacity	Nom.			kW	9.35(1)/9.10(2)	11.6(1)/11.5(2)	128(1)/12.7(2)	140(1)/15.3(2)
Heating capacity	Nom.			kW	9.37(3)/9.00(4)	10.6(3)/9.82(4)	120(3)/12.5(4)	16.0(3)/16.0(4)
Power input	Cooling	Nom.		kW	2.79(1)/1.71(2)	3.56(1)/2.17(2)	4.06(1)/2.51(2)	4.58(1)/3.24(2)
	Heating	Nom.		kW	1.91(3)/2.43(4)	2.18(3)/2.68(4)	2.46(3)/3.42(4)	3.53(3)/4.56(4)
Capacity control	Method				Variable (inverter)			
EER					3.35(1)/5.34(2)	3.26(1)/5.31(2)	3.16(1)/5.04(2)	3.06(1)/4.74(2)
COP					4.91(3)/3.71(4)	4.83(3)/3.66(4)	4.87(3)/3.64(4)	4.53(3)/3.51(4)
Dimensions	Unit	Height		mm	870			
		Width		mm	1,380			
		Depth		mm	460			
Weight	Unit			kg	147			
Water heat exchanger	Type				Plate heat exchanger			
	Water volume			l	2			
Air heat exchanger	Type				High efficiency fin and tube type with integral subcooler			
Compressor	Type				Hermetically sealed swing inverter compressor			
	Quantity				1			
Fan	Type				Propeller fan			
	Quantity				1			
	Air flow rate	Cooling	Nom.	m³/min	63	70	85	
Heating		Nom.	m³/min	48.0	55.8	70.4	85.0	
Sound power level	Cooling	Nom.		dBA	65.5	670	69.0	
Sound pressure level	Cooling	Nom.		dBA	44.0	477	50.8	510
Operation range	Air side	Cooling	Min.~Max.	°CDB	10 ~43			
		Heating	Min.~Max.	°CDB	-25 ~25			
	Water side	Cooling	Min.~Max.	°CDB	5 ~22			
		Heating	Min.~Max.	°CDB	9 (6)~60 (6)			
	Refrigerant	Type/GWP				R-32/675.0		
Control				Electronic expansion valve				
Circuits		Quantity			1			
Refrigerant charge	Per circuit			kg	3.80			
				TCO2Eq	2.6			
Unit	Running current	Max		A	14.0			
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400			

(1)Cooling: EW 12°C; LW 7°C; ambient conditions: 35°CDB | (2)Cooling: EW 23°C; LW 18°C; ambient conditions: 35°CDB | (3)Condition: Ta DB/WB 7°C/6°C - LWC 35°C (DT = 5°C) | (4)Condition: Ta DB/WB 7°C/6°C - LWC 45°C (DT=5°C) | (5)According to EN14825 | (6)For more details, see operation range drawing | Depends on operation mode, refer to installation manual.

Air cooled mini inverter heat pump

- Choosing for an R-32 product, reduces the environmental impact with 68% compared to R-410A and leads directly to lower energy consumption thanks to its high energy efficiency
- Inverter chiller
- Hermetically sealed swing inverter compressor
- New casing for the outdoor units
- Separate MMI-2 controller for indoor installation



EWAA-EWYA-D_R

Heating & Cooling				EWYA-D	009DW1P-H-		011DW1P-H-		014DW1P-H-		016DW1P-H-	
Space cooling	A Condition Pdc 35°C			kW	9.35		116		128		14.0	
	ηs,c			%	222		229		226		221	
SEER					5.62(5)		5.79(5)		5.71(5)		5.59(5)	
 Space heating	Average climate water outlet 35°C	General	SCOP		4.82		4.73		4.70		4.69	
			Seasonal space heating eff. class		A+++							
Cooling capacity	Nom.			kW	9.35(1)/9.10(2)		116(1)/11.5(2)		128(1)/12.7(2)		140(1)/15.3(2)	
Heating capacity	Nom.			kW	9.37(3)/9.00(4)		10.6(3)/9.82(4)		120(3)/12.5(4)		16.0(3)/16.0(4)	
Power input	Cooling	Nom.		kW	2.79(1)/1.71(2)		3.56(1)/2.17(2)		4.06(1)/2.51(2)		4.58(1)/3.24(2)	
	Heating	Nom.		kW	1.91(3)/2.43(4)		2.18(3)/2.68(4)		2.46(3)/3.42(4)		3.53(3)/4.56(4)	
Capacity control	Method				Variable (inverter)							
EER					3.35(1)/5.34(2)		3.26(1)/5.31(2)		3.16(1)/5.04(2)		3.06(1)/4.74(2)	
COP					4.91(3)/3.71(4)		4.83(3)/3.66(4)		4.87(3)/3.64(4)		4.53(3)/3.51(4)	
Dimensions	Unit	Height		mm	870							
		Width		mm	1,380							
		Depth		mm	460							
Weight	Unit			kg	147							
Water heat exchanger	Type				Plate heat exchanger							
	Water volume			l	2							
Air heat exchanger	Type				High efficiency fin and tube type with integral subcooler							
Compressor	Type				Hermetically sealed swing inverter compressor							
	Quantity				1							
Fan	Type				Propeller fan							
	Quantity				1							
	Air flow rate	Cooling	Nom.	m³/min	63	70		85				
Heating		Nom.	m³/min	48.0	55.8		70.4		85.0			
Sound power level	Cooling	Nom.		dBA	65.5	670		69.0				
Sound pressure level	Cooling	Nom.		dBA	44.0	477		50.8		510		
Operation range	Air side	Cooling	Min.~Max.	°CDB	10 ~43							
		Heating	Min.~Max.	°CDB	-25 ~25							
	Water side	Cooling	Min.~Max.	°CDB	5 ~22							
		Heating	Min.~Max.	°CDB	9 (6)~60 (6)							
	Refrigerant			Type/GWP	R-32/675.0							
				Control	Electronic expansion valve							
			Circuits	Quantity	1							
Refrigerant charge	Per circuit			kg	3.80							
				TCO2Eq	2.6							
Unit	Running current	Max		A	14.0							
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400							

(1)Cooling: EW 12°C; LW 7°C; ambient conditions: 35°CDB | (2)Cooling: EW 23°C; LW 18°C; ambient conditions: 35°CDB | (3)Condition: Ta DB/WB 7°C/6°C - LWC 35°C (DT = 5°C) | (4)Condition: Ta DB/WB 7°C/6°C - LWC 45°C (Dt=5°C) | (5)According to EN14825 | (6)For more details, see operation range drawing | Depends on operation mode, refer to installation manual.

Air cooled mini inverter heat pump

- Choosing for an R-32 product, reduces the environmental impact with 68% compared to R-410A and leads directly to lower energy consumption thanks to its high energy efficiency
- Inverter chiller
- Hermetically sealed swing inverter compressor
- New casing for the outdoor units
- Separate MMI-2 controller for indoor installation



Inverter technology



Swing compressor

EW(A-Y)A004-008DV3P-H_R

Heating & Cooling				EWYA-D	004DV3P-H	006DV3P-H	008DV3P-H	009DV3P-H-	011DV3P-H-	014DV3P-H-	016DV3P-H-
Space cooling	A Condition Pdc 35°C			kW				9.35	11.6	128	14.0
	ηs,c			%				222	229	226	221
SEER								5.62(8)	5.79(8)	5.71(8)	5.59(8)
 Space heating	Average climate water outlet 35°C	General	SCOP Seasonal space heating eff. class		4.54	4.52	4.61	4.82	4.73	4.70	4.69
					A+++						
Cooling capacity	Nom.			kW	4.86(1)/4.52(2)	5.83(1)/5.09(2)	6.18(1)/5.44(2)	9.35(4)/9.10(5)	11.6(4)/11.5(5)	128(4)/127(5)	14.0(4)/15.3(5)
Heating capacity	Nom.			kW	4.30(1)/4.60(2)	6.00(1)/5.90(2)	7.50(1)/7.80(2)	9.37(6)/9.00(7)	10.6(6)/9.82(7)	120(6)/125(7)	16.0(6)/16.0(7)
Power input	Cooling	Nom.		kW	0.820(1)/1.36(2)	1.08(1)/1.55(2)	1.19(1)/1.73(2)	2.79(4)/1.71(5)	3.56(4)/2.17(5)	4.06(4)/2.51(5)	4.58(4)/3.24(5)
	Heating	Nom.		kW	0.840(1)/1.26(2)	1.24(1)/1.69(2)	1.63(1)/2.23(2)	1.91(6)/2.43(7)	2.18(6)/2.68(7)	2.46(6)/3.42(7)	3.53(6)/4.56(7)
Capacity control	Method				Variable (inverter)						
EER					5.91(1)/3.32(2)	5.40(1)/3.28(2)	5.19(1)/3.14(2)	3.35(4)/5.34(5)	3.26(4)/5.31(5)	3.16(4)/5.04(5)	3.06(4)/4.74(5)
COP					5.10(1)/3.65(2)	4.85(1)/3.50(2)	4.60(1)/3.50(2)	4.91(6)/3.71(7)	4.83(6)/3.66(7)	4.87(6)/3.64(7)	4.53(6)/3.51(7)
Dimensions	Unit	Height		mm	770			870			
		Width		mm	1,250			1,380			
		Depth		mm	362			460			
Weight	Unit			kg	88.0			147			
Water heat exchanger	Type				Plate heat exchanger						
Air heat exchanger	Water volume			l	1			2			
	Type				-			High efficiency fin and tube type with integral subcooler			
Compressor	Type				Hermetically sealed swing compressor			Hermetically sealed swing inverter compressor			
	Quantity							1			
Fan	Type				Propeller fan						
	Quantity				1						
	Air flow rate	Cooling	Nom.	m³/min	-			63	70	85	
Heating		Nom.	m³/min	-			48.0	55.8	70.4	85.0	
Sound power level	Cooling	Nom.		dBA	61.0(1)	62.0(1)		65.5	67.0	69.0	
	Heating	Nom.		dBA	58.0(1)	60.0(1)	62.0(1)	-			
Sound pressure level	Cooling	Nom.		dBA	48.0(1)	49.0(1)	50.0(1)	44.0	47.7	50.8	51.0
	Heating	Nom.		dBA	44.0(1)	47.0(1)	49.0(1)	-			
Operation range	Air side	Cooling	Min.~Max.	°CDB	10(3)~43			10~43			
		Heating	Min.~Max.	°CDB				-25~25			
Refrigerant	Type/GWP				R-32/675.0						
Refrigerant charge	Charge			kg	135			-			
	Control				-			Electronic expansion valve			
	Circuits	Quantity			-			1			
Refrigerant charge	Per circuit			kg	-			3.80			
Unit	Running	Max		A	-			30.8			
Power supply	Phase/Frequency/Voltage			Hz/V	1~/50/230 +/-10%			1~/50/230			

(1)Condition 1: cooling Ta 35°C - LWE 18°C (DT = 5°C); heating Ta DB/WB 7°C/6°C - LWC 35°C (DT = 5°C) | (2)Condition 2: cooling Ta 35°C - LWE 7°C (DT = 5°C); heating Ta DB/WB 7°C/6°C - LWC 45°C (DT = 5°C) | (3)For more details, see operation range drawing | (4)Cooling: EW 12°C; LW 7°C; ambient conditions: 35°CDB | (5)Cooling: EW 23°C; LW 18°C; ambient conditions: 35°CDB | (6)Condition: Ta DB/WB 7°C/6°C - LWC 35°C (DT = 5°C) | (7)Condition: Ta DB/WB 7°C/6°C - LWC 45°C (Dt=5°C) | (8)According to EN14825 | Depends on operation mode, refer to installation manual.

