

Perfera

FTXM + RXM



Comfort režim rada



3D protok vazduha



Tihi rad spoljne jedinice



Titanijum apatitski filter, srebrni filter



Mogućnost povezivanja sa multi sistemima

perfera

- › Privlačan, futuristički dizajn
- › Čist vazduh bez alergena tokom cele godine
- › Tajmer za programiranje rada uređaja na nedeljnom nivou
- › Ravnomerna temperatura u prostoriji zahvaljujući 3D protoku vazduha
- › Nečujan rad jedinice
- › Koristi ekološki freon R-32 koji direktno utiče na smanjenje potrošnje električne energije

FTXM + RXM

Energetska efikasnost do

A+++



Podaci o efikasnosti			FTXM + RXM	CTXM15R	20R + 20R	25R + 25R	35R + 35R	42R + 42R	50R + 50R	60R + 60R	71R + 71R
Kapacitet hlađenja	Min./Nom./Maks.		kW	Samo kod multi sistema	1,3/2,0/2,6	1,3/2,5/3,2	1,4/3,4/4,0	1,7/4,2/5,0	1,7/5,0/6,0	1,7/6,0/7,0	2,3/7,1/8,5
Kapacitet grejanja	Min./Nom./Maks.		kW		1,3/2,5/3,5	1,3/2,8/4,7	1,4/4,0/5,2	1,7/5,4/6,0	1,7/5,8/7,7	1,7/7,0/8,0	2,3/8,2/10,2
Apsorbovana snaga	Hlađenje	Nom.	kW		0,44	0,56	0,80	0,97	1,36	1,77	2,34
	Grejanje	Nom.	kW		0,50	0,56	0,99	1,31	1,45	1,94	2,57
Sezonska efikasnost (u skladu sa EN14825)	Hlađenje	Oznaka energetske efikasnosti			A+++			A++			
		Pdesign	kW		2,00	2,50	3,40	4,20	5,00	6,00	7,10
		SEER			8,65	8,65	8,65	7,85	7,41	6,90	6,20
		Godišnja potrošnja energije	kWh		81	101	137	187	236	304	401
	Grejanje (prosečna klima)	Oznaka energetske efikasnosti			A+++			A++		A+	A+
		Pdesign	kW		2,30	2,40	2,50	4,00	4,60	4,80	6,20
		SCOP/A			5,00			4,71		4,30	4,1
			Godišnja potrošnja energije		kWh	631	659	686	1.189	1.368	1.562

Unutrašnja jedinica				FTXM	CTXM15R	20R	25R	35R	42R	50R	60R	71R
Dimenzije	Uređaj	Visina x Širina x Dubina	mm	295x778x272						299x998x292		
Filter za vazduh	Tip	Uklonjiv/periv/otporan na buđ										
Nivo zvučnog pritiska	Hlađenje	Visoko/Nisko/Tihi rad	dBA	41/25/19			45/29/19		45/30/21	44/36/27	46/37/30	47/38/35
	Grejanje	Visoko/Nisko/Tihi rad	dBA	39/26/20		39/27/20		39/28/20	45/29/21	43/34/31	45/36/33	46/37/34

Spoljna jedinica				RXM		20R	25R	35R	42R	50R	60R	71R
Dimenzije	Uređaj	Visina x Širina x Dubina	mm			550x765x285					734x870x373	
Nivo zvučnog pritiska	Hlađenje	Visoko/Tihi rad	dBA			46		49	48		48	47
	Grejanje	Visoko/Tihi rad	dBA			47		49	48		49	48
Radni opseg	Hlađenje	Spoljna temp. Min.~Maks.	°CDB	Samo kod multi sistema		-10~50						-10~50
	Grejanje	Spoljna temp. Min.~Maks.	°CWB			-20~25						-15~25
Freon	Tip / Punjenje/ GWP	Punjenje: kg / TCO _{eq}				R-32/0,76/ 0,5/675				R-32/1,30/0,9/675		R-32/1,45/1,0/675
Povezivanje cevi	Dužina cevi	SJ - UJ Maks.	m			20				30		
	Visinska razlika	UJ - SJ Maks.	m			15				20		
Struja - 50Hz	Maksimalna jačina osigurača (MFA)*		A			10					15	20

