


Stylish

FTXA (AS) + RXA



Koanda efekat
u režimu hlađenja



Koanda efekat
u režimu grejanja



Senzor Grid eye



Online kontrola



Mogućnost
povezivanja sa multi
sistemima

stylish

- › Kompaktan dizajn u elegantnoj beloj, srebrnoj ili crnoj boji
- › Savršena raspodela temperature zahvaljujući Koanda efektu
- › Senzor Grid eye: prilagođava protok vazduha kada uoči razliku u temperaturi
- › Tehnologija Flash Streamer: moćno prečišćavanje vazduha
- › Skoro nečujan uređaj
- › Upravljanje uređajem putem aplikacije
- › Koristi freon R-32 koji ima smanjen negativni uticaj na životnu sredinu
- › Sezonska efikasnost do A+++ u hlađenju i grejanju

FTXA + RXA

Energetska efikasnost

A+++



FTXA-AS



RXA20-35A



ARC466A58

Podaci o efikasnosti			FTXA + RXA	CTXA15AW	20AW + 20A	25AW + 25A	35AW + 35A	42AW + 42B	50AW + 50B
Kapacitet hlađenja	Nom.		kW	Samo kod multi sistema	2,0	2,5	3,4	4,2	5
Kapacitet grejanja	Nom.		kW		2,5	2,8	4,0	5,4	5,8
Apsorbovana snaga	Grejanje	Nom.	kW		0,50	0,56	0,99	1,31	1,45
Sezonska efikasnost (u skladu sa EN14825)	Hlađenje	Oznaka energetske efikasnosti			A+++			A++	
		Pdesign	kW		2,00	2,50	3,40	4,20	5,00
		SEER			8,75	8,74	8,73	7,50	7,33
		Godišnja potrošnja energije	kWh		80	101	137	196	239
	Grejanje (prosečna klima)	Oznaka energetske efikasnosti			A+++			A++	
		Pdesign	kW		2,40	2,45	2,50	3,80	4,00
		SCOP/A			5,15			4,60	
		Godišnja potrošnja energije	kWh		653	666	680	1.156	1.217
Unutrašnja jedinica			FTXA	CTXA15AW	20AW	25AW	35AW	42AW	50AW
Dimenzije	Uređaj	Visina x Širina x Dubina	mm	295x798x189					
Filter za vazduh	Tip			Uklonjiv/periv					
Nivo zvučnog pritiska	Hlađenje	Visoko/Nisko/Tihi rad		39/25/19		40/25/19	41/25/19	45/29/21	46/31/24
	Grejanje	Visoko/Nisko/Tihi rad		39/25/19		40/25/19	41/25/19	45/29/21	46/31/24
Spoljna jedinica			RXA		20A	25A	35A	42B	50B
Dimenzije	Uređaj	Visina x Širina x Dubina	mm	Samo kod multi sistema	550x765x285			735x825x300	
Nivo zvučnog pritiska	Hlađenje	Visoko	dBA		46		49	48	
Radni opseg	Hlađenje	Spoljna temp. Min.-Maks.	°CDB		-10 ~ 46				
	Grejanje	Spoljna temp. Min.-Maks.	°CWB		-15 ~ 18				
Freon	Tip / Punjenje/ GWP		kg/TCO ₂ Eq		R-32/0,76/0,51/675			R-32/1,3/0,88/675	
Povezivanje cevi	Dužina cevi	SJ - UJ	Maks.		20			30	
	Visinska razlika	UJ - SJ	Maks.		15			20	
Struja - 50Hz	Maksimalna jačina osigurača (MFA)*		A		10	13		16	

