



Comfora

FTXP + RXP



Comfort režim rada



Econo režim rada za
uštedu energije



Tihi rad spoljne
jedinice



Titanijum apatitski
filter; srebrni filter



Mogućnost
povezivanja sa multi
sistemima

comfora

Diskretna zidna jedinica koja pruža visoku efikasnost i udobnost

- › Praktično nečujno
- › Onlajn kontroler (opciono)
- › Srebrni filter za uklanjanje alergena i prečišćavanje vazduha
- › 3D protok vazduha: vazduh se duva u sve uglove prostorije
- › Idealno za montažu iznad vrata
- › Bluevolution serija: manji uticaj na životnu sredinu
- › Sezonske vrednosti efikasnosti do A++ u hlađenju i grejanju
- › Savremeni zidni dizajn koji štedi prostor

FTXP + RXP

Energetska efikasnost do

A++



Podaci o efikasnosti			FTXP + RXP	20N + 20N	25N + 25N	35N + 35N	50N + 50N	60N + 60N	71N + 71N
Kapacitet hlađenja	Min./Nom./Maks.	kW		1,3/2,0/2,6	1,3/2,5/3,0	1,3/3,5/4,0	1,7/5,0/6,0	1,7/6,0/7,0	2,3/7,1/7,3
Kapacitet grejanja	Min./Nom./Maks.	kW		1,3/2,5/3,5	1,3/3,0/4,0	1,3/4,0/4,8	1,7/6,0/7,7	1,7/7,0/8,0	2,3/8,2/9,0
Apsorbovana snaga	Hlađenje	Min./Nom./Maks.	kW	0,31/0,50/0,72	0,31/0,65/0,72	0,29/1,0/1,30	0,32/1,38/1,83	0,33/1,82/2,98	0,45/2,69/3,27
	Grejanje	Min./Nom./Maks.		0,25/0,52/0,95	0,25/0,69/0,95	0,29/1,00/1,29	0,44/1,58/2,36	0,45/1,93/2,78	0,62/2,57/3,30
Sezonska efikasnost (u skladu sa EN14825)	Hlađenje	Oznaka energetske efikasnosti		A++			A++		A++
		Pdesign	kW	2,00	2,50	3,50	5,00	6,00	7,10
		SEER		7,20	7,20	7,20	7,30	6,82	6,20
	Grejanje (prosečna klima)	Godišnja potrošnja energije	kWh	97	121	170	240	308	401
		Oznaka energetske efikasnosti		A++			A+		A+
		Pdesign	kW	2,20	2,40	2,80	4,60	4,80	6,20
		SCOP/A		4,65	4,61	4,64	4,10		4,01
		Godišnja potrošnja energije	kWh	663	728	845	1,463	1,638	2,166

Unutrašnja jedinica			FTXP	20N	25N	35N	50N	60N	71N
Dimenzije	Uređaj	Visina x Širina x Dubina	mm	286x770x225			295x990x263		
Filter za vazduh	Tip			Uklonjiv/periv			Uklonjiv/periv		
Nivo zvučnog pritiska	Hlađenje	Visoko/Nisko/Tihi rad	dBA	39/25/19	40/26/19	43/27/20	43/34/27	45/36/30	46/37/32
	Grejanje	Visoko/Nisko/Tihi rad	dBA	39/28/21	40/28/21	40/29/21	42/33/30	44/35/32	45/36/33

Spoljna jedinica			RXP	20N	25N	35N	50N	60N	71N
Dimenzije	Uređaj	Visina x Širina x Dubina	mm	550x658x275			734x870x373		
Nivo zvučnog pritiska	Hlađenje	Visoko	dBA	46		48	47	49	52
	Grejanje	Visoko	dBA	47		48	49	49	58
Radni opseg	Hlađenje	Spoljna temp. Min.~Maks.	°CDB	-10~46			-10~46		
	Grejanje	Spoljna temp. Min.~Maks.	°CWB	-15~18			-15~18		
Freon	Tip / Punjenje/ GWP	Punjenje: kg / TCO ₂ eq		R-32/0,55/0,37/675		R-32/0,70/0,48/675	R-32/0,90/0,61/675	R-32/1,150,78/675	R-32/1,150,78/675
Povezivanje cevi	Dužina cevi	SJ - UJ Maks.	m	15			30		
	Visinska razlika	UJ - SJ Maks.	m	12			20		
Struja - 50Hz	Maksimalna jačina osigurača (MFA)**	A		16			20		



Kompanija Daikin Europe N.V. učestvuje u programu sertifikacije Eurovent koji se odnosi na klima-uređaje (AC), agregate za hlađenje tečnosti (LCP), klima komore (AHU), i ventilator-konvektore (FCU). Proverite onaj tekstu važenje sertifikata. www.eurovent-certification.com ili www.certiflash.com



Heating&Cooling Expert d.o.o.
Official Daikin Sales Agent
Stanoja Glavaša 18 · 11000 Beograd
T. 011 6555 255 · office@hce.rs
www.daikin.rs



CLIMATE DESIGN D.O.O. Javorska 6, 11226 Beograd,
Tel: +38162290789, +38162290599
E-mail: veleprodaja@climatedesign.rs, www.climatedesign.rs

