

Emura

FTXJ (AW)



Senzor Intelligent
Eye za 2 zone



Comfort režim rada



3D protok vazduha



Online kontrola



Mogućnost
povezivanja sa multi
sistemima

emura

- › Srebrni filter za uklanjanje alergena i prečišćavanje vazduha hvata 99% alergena kao što su polen i grinje
- › 3D protok vazduha osigurava da vazduh dosegne i najudaljenije delove prostorije
- › Višezonsko inteligentno oko detektuje prisustvo ljudi u prostoriji
- › Upravljanje uređajem putem *online* aplikacije
- › Koristi ekološki freon R-32 koji direktno utiče na smanjenje potrošnje električne energije
- › Sezonska efikasnost do A+++ u hlađenju

FTXJ (AW)

Energetska efikasnost do

A+++



FTXJ-AW

ARC466A9

Unutrašnja jedinica				FTXJ	20AS+20AW+20AB+20A	25AS+25AW+25AB+25A	35AS+35AW+35AB+35A	42AS+42AW+42AB+42A	50AS+50AW+50AB+50A
Dimenzije	Jedinica	Visina x Širina x Dubina		mm	305 x900 x212				
Težina	Jedinica			kg	12				
Filter za vazduh	Tip	Uklonjiv/Periv							
Ventilator	Brzina protoka vazduha	Hlađenje	Tihi rad/ Nisko/Srednje/ Visoko	m³/min	4.6 /6.0 /8.4 /11.0	4.6 /6.0 /8.6 /11.4	4.6 /6.0 /8.6 /11.8	4.6 /7.2 /9.5 /13.0	5.2 /7.6 /10.4 /13.5
		Grejanje	Tihi rad/ Nisko/Srednje/ Visoko	m³/min	4.6 /6.4 /8.7 /11.1	4.6 /6.4 /9.0 /11.3	4.6 /6.4 /9.0 /11.7	5.2 /7.7 /10.5 /14.4	5.7 /8.2 /11.1 /15.0
Nivo zvučne snage	Hlađenje			dBA	57			60	
Nivo zvučnog pritiska	Hlađenje	Tihi rad/Nisko/Visoko		dBA	19 /25 /39	19 /25 /40	19 /25 /41	21 /29 /45	24 /31 /46
	Grejanje	Tihi rad/Nisko/Visoko		dBA	19 /25 /39	19 /25 /40	19 /25 /41	21 /29 /45	24 /33 /46
Kontrolni sistemi	Infracrveni daljinski upravljač				ARC488A1K				
	Žičani daljinski upravljač				BRC073A1				
Povezivanje cevi	Odvod				18				

